3580 Haven Avenue, Redwood City, California 94063 \* (650) 365-6567 Fax: (650) 365-5845 \* (800) 822-3940

E-mail: spectrex@spectrex.com
Web Site: www.spectrex.com

## **UV OZONE ANALYZER**

## **MODEL UV-100**



The model UV-100 ozone analyzer is for general purpose measurement of ozone in air. Its range is .002-100 ppm (v) with 2% accuracy, and it includes a built-in data logger. The UV-100 weighs only 2.1 kg (4.7 lb), it is powered by an AC adapter or 12 V external battery, and is equally versatile for the laboratory

or for process monitoring. The outputs are digital display, 0-2.5 VDC and 4-20 mA. The instrument features a low cost sample line filter with a Change Filter LED.

## **SPECIFICATIONS**

**UV Source:** 254 nm mercury lamp

Range: .002-100 ppm v/v in 3 ranges: 0-1.000 ppm, 0-10.00 ppm, 0-100.0 ppm

Outputs: Digital display, 0-2.5 V, 4-20 mA, data logging

Accuracy: 2%.

Sampling time: 10 seconds

**LED Indicators:** On-off, Recalibrate, Change Filter, >.1 ppm at sample area

**Size:** 95 mm X 210 mm X 216 mm (3.75" X 8.25" X 8.50")

**Weight:** 2.1 kg (4.7 lbs)

Power requirement: 12 volts DC at 400 mA.

Warranty: One year